



DuPont™ Styrofoam™ Brand Tape

Durable, Pliable Sealing Tape with Superior Tack

FEATURES/BENEFITS

Description

Styrofoam™ Brand Tape from DuPont is a durable sealing tape with excellent adhesion properties to help protect homes and building against moisture and air intrusion. **Styrofoam™ Brand Tape** is pliable – ensuring a tight seal, even at extremely low temperatures – and its oriented polypropylene backing is formulated with a UV-treated film to help resist degradation from exposure to sunlight.

Styrofoam™ Brand Tape is the recommended tape for sealing joints and seams of Styrofoam™ Brand insulated sheathings. It provides a permanent tight bond to sheathing boards to seal seams and enhance resistance to moisture and air infiltration.

Ease of Use

Styrofoam™ Brand Tape offers the qualities both professionals and do-it-yourselfers look for:

- Excellent tack with enhanced grip
- Strong, durable and impact resistant
- Pliable, for a tight seal even at low temperatures

- Versatile and easy to apply
- UV resistant

Sustainable Solutions

Styrofoam™ Brand Tape can be used to repair damaged foam insulation, reducing material costs and job-site waste. For the greatest energy savings potential and weather resistance, tape or patch any tears, holes, breaks or damage created during normal construction.

Complete System

Styrofoam™ Brand Tape is part of the complete lineup from DuPont – products designed to enhance the performance of the building envelope.

Available Sizes

Styrofoam™ Brand Tape is available in the size as shown in Table 1. A limited 10-year warranty is available as described at building.dupont.com/warranties.

TABLE 1: Packaging Specifications

Product Description	Box	Roll Weight	Outside Box Dimensions	Box Weight
3 3/4" x 165'	12 Rolls	14.4 oz	10" x 9 1/2" x 12"	12.0 lb

¹ Rolls are individually shrink-wrapped with a label on film and tape core.

PROPERTIES

Styrofoam™ Brand Tape exhibits physical properties as indicated in Table 2 when tested as represented. Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact DuPont at 1-866-583-2583 when additional guidance is required for writing specifications that include this product.

TABLE 2: Typical Physical Properties of Styrofoam™ Brand Tape

Property	Typical Value	Units
Width 3 3/4	< 1	in.
Length	165	ft.
Color	Clear	-
Backing	Oriented Polypropylene UV-treated Film	-
Adhesive	Acrylic	-
Shelf Life After Purchase	12	Months
<u>Typical Adhesion, ASTM D3330</u> Stainless Steel	75	oz/in, min
Tensile Strength, ASTM D882	20	lb/in, min.
Elongation	125	%
Installation Temperature	15 to 120	°F
Temperature Resistance	-40 to 220	°F

INSTALLATION

Use Conditions

- Apply to clean and dry surfaces, after evaporation of morning dew.
- Apply at temperatures over 15°F. After application, tape will perform in temperatures of -40°F to 220°F.
- Taping horizontal seams is recommended just prior to siding.
- When sealing the joints between two boards of insulated sheathing, center the tape over the joint to cover nails on both sides.

Application

1. Holding the roll in one hand, unroll a few inches of tape and position it at the top or one end of a seam or joint.
2. Press down with the other hand to adhere the first several inches.
3. Move down or along the wall, pulling the tape and applying pressure at the same time.
4. Seal all the way to the bottom or edge of the seam or joint. Trim with utility knife.
5. Continue until all joints and seams are taped.

Curing

- For best adhesion, apply pressure to the tape/sealed area.
- Maximum adhesion will be achieved after 72 hour cure.
- After each use, fold 1 inch of the tape end onto itself. Before reusing the tape, trim the folded end with a utility knife or scissors.

Equipment

For maximum protection against air infiltration and moisture, use Great Stuff Pro™ Gaps & Cracks in addition to DuPont™ Styrofoam™ Brand Tape around ducts and other penetrations.



**For more information visit us at
building.dupont.com
or call 1-833-338-7668**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

DuPont Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

Great Stuff Pro™ Polyurethane Foam Sealant contains isocyanate and a flammable blowing agent. Read all instructions and (Material) Safety Data Sheet ((M)SDS), carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and safety glasses or goggles. Not for use in aviation, or food/beverage contact, or as structural support in marine applications. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as behind walls and under tub surrounds; this improper use of the product could result in the accumulation of flammable vapors and/or uncured material. Failure to follow the warnings and instructions provided with the product, and/or all applicable rules and regulations, can result in injury or death.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including DuPont can give assurance that mold will not develop in any specific system.