

# DuPont™ Tyvek® StuccoWrap®

Grooved Housewrap Engineered for Stucco Facades and EIFS Systems



## FEATURES/BENEFITS

### Description

DuPont™ Tyvek® StuccoWrap® is a weather-resistant barrier with an engineered, grooved surface designed to be installed as a drainage plane behind stucco facades and EIFS systems. With a specially engineered surface texture designed for traditional and synthetic stucco systems in both commercial and residential construction, Tyvek® StuccoWrap® helps reduce cracking, improve stucco curing and channel moisture out of the wall.

Tyvek® StuccoWrap® can be used as the primary weather barrier for traditional stucco and direct-applied stone masonry applications (including brick) requiring two-layer weather resistive barrier systems or an intervening layer over the primary weather resistive barrier. It is also acceptable for use behind traditional lapped cedar and cement siding applications up to four stories. Tyvek® StuccoWrap® boasts a long track record of proven performance and meets all major building codes by ICC-ES evaluation reports.

Tyvek® StuccoWrap® does not absorb water, helps maintain the moisture level needed for better curing and doesn't expand and contract, resulting in a stronger stucco. Instead, Tyvek® StuccoWrap® provides superior water drainage, combats moisture accumulation and helps prevent air infiltration and exfiltration – helping to protect the installed R-value of insulation for more comfortable, energy efficient homes and buildings.

### Ease of Use

Tyvek® StuccoWrap® is lightweight, easy to handle and quick to install. It is pliable – wrapping around corners with ease – and easily interfaces at joints and over architectural elements. Some other features and benefits include:

- 30% more flexural strength than stucco cured on 60-minute building paper
- Good tear strength – 3X stronger than paper
- High water resistance – retains durability when wet and channels water to the outside
- Non-absorptive – does not absorb water out of curing stucco
- High vapor permeability promotes drying
- Outstanding air infiltration protection
- Sturdy, but easy to repair accidental damage with tape
- Not a food source for mold and mildew
- Withstands up to four (4) months (120 days) of UV exposure

### Available Sizes

Tyvek® StuccoWrap® is available in 5' x 200' rolls.

## High Performance Durability

DuPont™ Tyvek® StuccoWrap® ensures that the unique water management needs of stucco facades are covered without compromising building envelope performance. Tyvek® StuccoWrap® is highly inert, meaning stucco will not chemically react with or degrade it. Research has shown that when stucco is directly applied, Tyvek® StuccoWrap® is better than Grade D paper at managing hydration and remaining stable during curing<sup>1</sup>. These two features result in a significant reduction of cracking in the scratch coat, leading to better stucco integrity and a reduced chance for water to penetrate the facade.

<sup>1</sup> Development of a Textured Spun-bonded Polyolefin Water Barrier for Stucco and EIFS™ presented at an Innovative Products Symposium at the ASHRAE Winter Meeting, Atlanta, GA, January 2001.

## Sustainable Solutions

The use of a weather barrier as part of an assembly to reduce air infiltration may assist in achieving points for USGBC LEED® Certified Projects or an ENERGY STAR® label for new homes or home improvements.

## Complete System

Tyvek® StuccoWrap® along with DuPont™ Flashing Systems and other DuPont Weatherization Products provide integrated air and water and management solutions that help meet or exceed building and energy code requirements without sacrificing building durability.

## PROPERTIES

Tyvek® StuccoWrap® exhibits physical properties as indicated in Table 1 when tested as represented. Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact DuPont at 1-800-488-9835 when additional guidance is required for writing specifications that include this product.

**TABLE 1: Physical Properties for Tyvek® StuccoWrap®**

Test Method	Property	Typical Value	Units
ASTM E2178	Air Penetration Resistance	0.004	cfm/ft <sup>2</sup> @1.57 psf
Gurley Hill (TAPPI T-460)	Air Penetration Resistance	>300	sec/100cc
ASTM E1677	Air Penetration Resistance	Type 1	-
ICC-ES AC 24 Section 6.11	Drainage	Pass	-
ASTM E2273	Drainage	> 98	%
ICC-ES AC 235 Section 4.5	Drainage	Pass	-
ASTM E96-00 Method A	Water Vapor Transmission	250 36	g/m <sup>2</sup> -24 hrs perms
ASTM E96-00 Method B	Water Vapor Transmission	350 50	g/m <sup>2</sup> -24 hrs perms
AATCC 127	Water Penetration Resistance	210	cm
TAPPI T-410	Basis Weight	2.1	
ASTM D882	Breaking Strength	30/30	
ASTM D1117	Tear Resistance (Trapezoid)	7/9	
ASTM E84	Surface Burning Characteristics	5 Class A	Flame Spread Index
ASTM E84	Surface Burning Characteristics	25 Class A	Smoke Developed Index
-	Ultra Violet Light Exposure (UV)	120 (4)	days (months)

Note: These values represent roll averages. Individual roll results may differ due to normal manufacturing variations.

**WARNING:** DuPont™ Tyvek® is combustible and should be protected from an open flame and other high heat sources. If the temperature of DuPont™ Tyvek® reaches 750°F (400°C), it will burn and the fire may spread and fall away from the point of ignition.



**For more information visit us at  
tyvek.com  
or call 1-800-448-9835**

**NOTICE:** No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2021 DuPont.

43-D100134-enNA-0221 CDP